

# 32fes2019 Race Regulation

For Mini made until 2000 (except car participating to Historic race, 1.3i Challenge and 998Challenge)

	1300N (Normal)	Tuning		OPEN	M (MOTO)	
		1000T	1300T		FIVE	MOTO
Crankshaft / Con rod	Normal	Free		←	←	←
Piston and Bore size	Normal	Free		←	←	←
Engine capacity	Changing forbidden	1000T = less than 1020cc 1300T = less than 1300cc		Free	←	←
Cylinder head	Normal	Free (5 Port Head only)				Free
Rocker arm	Normal	Free		←	←	←
Camshaft / Valve System	Normal	Free		←	←	←
Air Cleaner	Free	←		←	←	←
ECU	Normal	Free		←	←	←
Exhaust	Free	←		←	←	←
Ignition System	Free	←		←	←	←
Cooling System	Free, if there is no change of location, numbers and movements principles	Free		←	←	←
Oil cooler	Free	←		←	←	←
Carburettor or Injector	Normal	Free		←	←	←
Transmission	Normal	Until 4th speed Sequential forbidden		Free	←	←
Differential	Normal	Free		←	←	←
Clutch	Normal	Free		←	←	←
Flywheel	Normal	Free		←	←	←
Shock absorbers	Free, if there is no change of location, numbers and movements principles	Free		←	←	←
Rubber Cone	Only Hi-Lo kit permitted	Free, if there is no change of location, numbers and movements principles			Free	←
Brake	Changing to cars on the same line permitted	Free		←	←	←
Suspension Stabilizer	Forbidden	Free		←	←	←
Camber and Caster angle	Normal	Free		←	←	←
Suspension Bush	Change of material permitted (Pillow ball forbidden)	Free		←	←	←
Tyre	Free, except for Slick	←		←	Free	←
Wheel	12 inch or less	←		13 inch or less	Free	←
Body	Remodelling forbidden	Only Inner fender and Front bulkhead processing permitted		(1)	Free	←
Bonnet / Boot	Normal	Weight saving permitted, Shape changing forbidden		Free	←	←
Wheel arch and other	Fixing Wheel arch permitted / Original non-wearing things like Aero parts forbidden				Free	←
Bumper	Normal	Removing permitted, including Steer			Free	←
Window glass material	Changing forbidden	Free, except for the Front			Changing permitted	←
Car compartment	Must be completely isolated from the Engine bay, Fuel tank, Oil tank, Gear box and Pipe seam					
Seat	Changing permitted, fix it with 4 points or more					
Interior	Door lining required	←		←	Free	←
Seatbelt	Full Harness type with 4 points or more required (Push buckle type forbidden)					
Roll Cage	Need Steel made pipes (outer diameter 38mm, thickness 2mm or more) with 6 points or more, and Side bar on the driver's side required. Make a 4mm diameter hole on the main Roll bar, and paint it in yellow (must be separated from curved, welded parts over 100mm or more).					
Fuel tank	Loading Safety tank authorized by FIA / JAF, or admitted by Mini Jack required					
Fuel pump	Free	←		←	←	←
Oil catch Tank	2L or more required (1L permitted for 1020cc or more)					
Circuit Breaker	Mounting required (must be able to shut all electricity from both inside and outside)					
Fire extinguisher	1.5kg or more required					
Battery	Moving permitted. Isolating terminal required, and must be fixed for sure. (c.f. Car compartment)					
Brake, Clutch master	Taping required, so that the cap won't open or fluid won't leak					
Towing Hook	Front and Rear required					
Minimum Car weight	610kg	590kg		585kg		

\* The car cannot run if the Organizer judges it is not enough safe.

\*This regulation may change without announcement.

(1)For sections forward the Scuttle panel, a minimum of body remodelling is allowed to bring air into the engine room. For the interior too, seat's crossmember and rear pocket/rear seat panel remodelling are also allowed.