32fes2019 Race Regulation

Historic car race

(1500 Under class / 1500 Over class)

For British, French, Italian car made until 1975. American, German and Japanese car made until 1970 (Direct or Remote type Mini recommended)

Car specially accepted by the Organizer are also permitted

| | GOOD WOOD | HISTORIC | HISTORIC MOTO |
|--------------------------|---|----------------------------|---------------|
| Crankshaft / Con rod | Changing Stroke forbidden | Free | ← |
| Piston and Bore size | Free | ← | ← |
| Engine capacity | 1500 Under···less than 1500cc | / 1500 Over…1500cc or more | Free |
| Engine and Cylinder head | Body, Chassis, Engine, Gear box must be the same as the original product | | Free |
| Camshaft / Valve System | Free | ← | ← |
| Air Cleaner | Free | ← | ← |
| Exhaust | Silencer required | ← | Free |
| Ignition System | Using distributor required | Free | Free |
| Gooling System | Free | ← | ← |
| Oil cooler | Free | ← | ← |
| Intake System | Free (changing to Elect | ric Injection forbidden) | Free |
| Supercharger | Only originally loaded one permitted | | Free |
| Transmission | Changing ratios from the Original product forbidden | Free, but until 5 Forward | Free |
| Differential | Free | ← | ← |
| Clutch | Free | ← | ← |
| Flywheel | Free | ← | ← |
| Suspension | Free | ← | ← |
| Brake | Free | ← | ← |
| Suspension Stabilizer | Free | ← | ← |
| Suspension Bush | Pillow ball forbidden | Free | ← |
| Tyre | DUNLOP G5, CR65, CR70 only | Free, except for Slick | Free |
| Wheel | Until 2 inches up compared to the original product (must be 10 inch for Mini) | | Free |
| Body | Remodelling forbidden (smallest processing is permitted to load a Safety tank) Free (must have enough toughness) | | |
| Bonnet/Boot | Changing material permitted | ← | Free |
| Wheel arch | Mounting permitted, for Mini and N360 only | ← | Free |
| Bumper | Changing permitted, including Steer | ← | Free |
| Window glass material | (1) | ← | Free |
| Car compartment | Must be completely isolated from the Engine bay, Fuel tank, Oil tank, Gear box and Pipe seam | | |
| Seat | Changing permitted, fix it with 4 points or more | Full bucket Seat required | ← |
| Seatbelt | Full Harness type with 4 points or more required (Push buckle type forbidden) | | |
| HANS | Using HANS strongly recommended | | |
| Roll Cage | Steel made with 6 points or more required 3 points or more type may be accepted if the Organizer admit it, judging the shape of car | | |
| Fuel tank | Loading Fuel tank authorized by FIA / JAF, or admitted by Mini Jack required | | |
| Fuel pump | Free | ← | ← |
| Oil catch Tank | | 2L or more required | |
| Circuit Breaker | Strongly recommended Required | | |
| Fire extinguisher | 1.5kg or more required | | |
| Battery | Moving permitted. Isolating terminal required, and must be fixed for sure. (c.f. Car compartment) | | |
| Brake, Clutch master | Taping required, so that the cap won't open or fluid won't leak | | |
| Towing Hook | Front and Rear required | | |

^{*} The car cannot run if the Organizer judges it is not enough safe.

^{*}This regulation may change without announcement.

⁽¹⁾ Changing to clear material permitted, except for the front. For Convertible cars, changing the front is also permitted.